


Frame filter



Applications

For pre- and fine dust filtration in

- Aerial engineering plants and devices of all kinds
- Air conditioning and paint shops

Classification acc. to EN 779

- | | |
|--------------------------|--------------------|
| ▪ Panel filter G2 | ▪ Z-Line G4 |
| ▪ Panel filter G3 | ▪ Z-Line F5 |
| ▪ Panel filter G4 | ▪ Z-Line F6 |
| ▪ Panel filter F5 | ▪ Z-Line F7 |
| | ▪ Z-Line F8 |
| | ▪ Z-Line F9 |


Versions

- Standard sizes with stamped cardboard frame (G4 only)
- Special sizes on request
- Frame types: cardboard frame, galvanized metal frame, aluminium frame, plastic frame
- Panel filters also available as "Dust-Stop" version
- Optional with gasket
- Z-Line special sizes or with fine filtration media are additionally equipped with metal expanded mesh on clean air side

Material characteristics


- Tested according to EN 779
- Fire prevention requirements according to DIN 53438-3 (F1)
- Humidity resistant up to 100% r. h.
- Temperature resistant up to max. 80°C depending on type of frame

Benefits of VOLZ Filters




Z-line characteristics

- Big filter area in small required space



Z-line Ex-Protect

- Z-line is also available as Ex-Protect version for aerial engineering plants of Ex-Schutz zones 1 and 2 (only metal frame)
- With metal expanded mesh on both sides
- Electroconductive medium



Combination possible


- Changing frame (only metal frame) can be used with several filter mats




- Filter media is produced in-house
- Quality control of the complete production with internal filter test equipment and modern quality-management-tools

Standard versions frame filter G2 - F9			
Width x Height	Depth	Filter area panel filter	Filter area Z-line
	mm	m²	m²
290 x 594 mm	24**	0.17	*
	48	0.17	0.6
	96	0.17	1.0
393 x 495 mm	24**	0.19	*
	48	0.19	0.7
	96	0.19	1.3
393 x 622 mm	24**	0.24	*
	48	0.24	0.9
	96	0.24	1.3
495 x 495 mm	24**	0.25	*
	48	0.25	0.9
	96	0.25	1.7
495 x 622 mm	24**	0.31	*
	48	0.31	1.1
	96	0.31	1.7
594 x 594 mm	24**	0.36	*
	48	0.36	1.3
	96	0.36	2.0

▪ Panel filter: G2 - F5
 ▪ Z-Line: G4 - F9
 * Special sizes on request
 ** Cardboard frames with 24 mm
 Other frame types with 25 mm



Panel filter Dust-Stop 594 x 594 x 48mm; G3		Z-line - filter 594 x 594 x 48mm; G4	
Initial pressure drop (Pa)	35	Initial pressure drop (Pa)	85
Recommended final pressure drop (Pa)	250	Recommended final pressure drop (Pa)	250
Nominal air flow rate (m³/h)	2000	Nominal air flow rate (m³/h)	3400
Average arrestance (%)	80 - 90	Average arrestance (%)	≥ 90



VOLZ Luftfilter GmbH & Co. KG

Robert-Bosch-Straße 25
D-72160 Horb am Neckar

Phone: +49 7451 5516-0
Fax: +49 7451 5516-120

info@volzfilters.com
www.volzfilters.com

All information, images and pictures are property of VOLZ Luftfilter GmbH & Co. KG and are provided to the best knowledge. However VOLZ Luftfilter GmbH & Co. KG does not guarantee the completeness or correctness and cannot be held responsible for damages caused by the recipient's usage or his confidence in the completeness or correctness of the information. The stated data contains average values with tolerances as a result of production irregularities; therefore it does not relieve the recipient of own examination and tests. For the correctness of the information in particular cases, an explicit and written affirmation through VOLZ Luftfilter GmbH & Co. KG is required. Furthermore, the data serves as a service description and cannot be interpreted as warranted properties or durabilities.